


## Downlight Slim SQ

IP20

3 años  
GARANTÍA  
WARRANTY

30000h

ULTRA  
SLIMEmpotrable  
Recessed

### Características / Characteristics

Downlight empotrable con diseño ultradelgado cuadrado. Su diseño sin carcasa, es ideal para aplicaciones en cielorrasos con tan solo 2 pulgadas de espacio libre. Es sencillo y rápido de instalar.

La serie Slim Square ofrece una amplia gama de tamaños y potencias siendo una de las favoritas entre diseñadores y arquitectos.

*Indoor recessed downlight with ultra-slim squared design. Its housing-free design is ideal for installation in ceilings with as little as 2 inches of clearance. It is easy and simple to install. The Slim Square Series offers a wide range of sizes and wattages making it a favorite among designers and architects.*




### Información Técnica / Technical Information

#### Especificaciones / Specifications

Código SKU	Descripción Description	Potencia Power (W)	TCC CCT (K)	Flujo Luminoso Luminous Flux (lm)	Tensión Voltage (V~)	Ángulo de Apertura Beam Angle	IRC CRI	Factor de Potencia PF	Distorsión Armónica THD
68200612A	DOWNLIGHT EMPOTRAR 4"	6	6500	270	85-265 VAC	120°	> 70	> 0.5	< 20%
99999999A	DOWNLIGHT EMPOTRAR 5"	9		500					
68201212A	DOWNLIGHT EMPOTRAR 6"	12		600					
99999999A	DOWNLIGHT EMPOTRAR 7"	15		900					
68201812A	DOWNLIGHT EMPOTRAR 8"	18		1080					
68202412A	DOWNLIGHT EMPOTRAR 11"	24	1440						

### Dimensiones Generales / General Dimensions

Dimensión Nominal	A-B (mm)	C (mm)*	D (mm)
6W	118	105	10
9W	145	130	10
12W	168	155	10
15W	188	175	10
18W	220	205	10
24W	293	285	10



- \* Medida para corte / Cut out

### Fotometría / Photometry

