

GU10

Multi Voltage



- IP44 Damp Location
- Working temperature at -20°C~40°C
- Recommended use: 10-12 hours / day
To avoid product damage or voided warranty
- Indoor Use

CE	VOLTS 100-253	 30,000
 120° 38° Beam Angle	CRI 80	PF 0.50
Base GU10	 -20°C to 40°C	5 YEAR Warranty

	Beam	Box	Blister	W	CCT	Lumens	Diameter	Length	
	120°	AL572123	AL572182	4W	3000K	350lm	49.4mm	56.5mm	
		AL572124	AL572183		6500K	350lm	49.4mm	56.5mm	
	120°	AL572125	AL572184	6W	3000K	500lm	49.4mm	56.5mm	
		AL572325	AL572324		5000K	500lm	49.4mm	56.5mm	
		AL572126	AL572185		6500K	500lm	49.4mm	56.5mm	
	38°	AL572131	AL572186	4W	3000K	350lm	49.4mm	54mm	
		AL572132	AL572187		6500K	350lm	49.4mm	54mm	
	38°	AL572133	AL572188	6W	3000K	500lm	49.4mm	54mm	
		AL572134	AL572189		6500K	500lm	49.4mm	54mm	

Notes

- ± 3mm range in height / ± 2mm range in diameter
- Lumen/power tolerance = up to 10%

Packing information

For Color Box

Model	CBM (master)	Pieces per master	Master box (cm)
GU10	0.0253	100	57.3 x 29.1 x 15.2