

TUBO LED T8 ILUKON 18 W


PARA USO GENERAL

| | | |
|-------------------|--------------------------|-----------------|
| CRI IRC | VIDA Hrs LIFE Hrs | ANGULO ANGLE |
| 80 | 30.000 | 270° |
| EFICACIA EFFICACY | F. POTENCIA POWER FACTOR | VOLTAJE VOLTAGE |
| 100lm/w | ≥0,90 | 100-277V |



Conexión/ Connection

UTILIZAR SOLO BASES NO PREPUENTEADAS
USE ONLY NON-SHUNTED LAMPHOLDERS



Descripción Tubo LED de uso general y alta eficiencia

Description LED Tube, for general use, high efficacy.

ILUKON
PROFESSIONAL LIGHTING



Dimensiones/ Dimensions

| Watts/ Watts | Código/ Code | Largo/ Length | Unidades por caja/ Units per box |
|-----------------|-----------------|------------------|-------------------------------------|
| 18W | 232118640 | 120 cm | 30 |

Especificaciones Fotométricas / Photometric Specifications

| Watts/ Watts | Código/ Code | Flujo Luminoso LED/ Luminous Flux LED | Temp. Color / CCT | Voltaje entrada/ Input Voltage | Factor de Potencia/ Power Factor | Vida útil hrs/ Lifetime hrs | Eficiencia/ Efficacy |
|-----------------|-----------------|--|----------------------|-----------------------------------|-------------------------------------|--------------------------------|-------------------------|
| 18W | 232118640 | 1800Lm | 6500K | 120-277V | 0.90 | 30.000 | 100 LPW |

NOTA: GLS se reserva el derecho de modificar o revisar las especificaciones técnicas sin previo aviso.
NOTE: GLS reserves the right to modify or revise technical specifications without prior notice.

Contacto: www.gls-ca.com / mail: contact@glsc.ca.com / tel: (506) 2434-1212 y (506) 2228-2222.

GLS
GLOBAL LIGHTING
SOLUTIONS S.A.
Master Distributor