

ILUKON BOMBILLO LED

PARA USO GENERAL



CRI
IRC

80

VIDA Hrs
LIFE Hrs

5.000

ANGULO
ANGLE

220°

EFICACIA
EFFICACY

87lm/w

F. POTENCIA
POWER FACTOR

≥0,50

VOLTAJE
VOLTAGE

100-130V



ILUKON
PROFESSIONAL LIGHTING



Especificaciones Fotométricas / Photometric Specifications

Código/ Code	Watts/ Watts	Flujo Luminoso LED/ Luminous Flux LED	Temp. Color / CCT	Voltaje entrada/ Input Voltage	Factor de Potencia/ Power Factor	Vida útil hrs/ Lifetime hrs	Eficiencia/ Efficacy
95019093A	9W	700 Lm	3000 K	100-130V	0.50	5.000	77 LPW
95019090A	9W	700 Lm	6000 K	100-130V	0.50	5.000	77 LPW
95019123A	12W	1055 Lm	3000 K	100-130V	0.50	5.000	87 LPW
95001912A	12W	1055 Lm	6000 K	100-130V	0.50	5.000	89 LPW

NOTA: GLS se reserva el derecho de modificar o revisar las especificaciones técnicas sin previo aviso.

NOTE: GLS reserves the right to modify or revise technical specifications without prior notice.

Contacto: www.gls-ca.com / mail: contact@gls/ca.com / tel: (506) 2434-1212 y (506) 2228-2222.

GLS
GLOBAL LIGHTING
SOLUTIONS S.A.
Master Distributor