QOT2020

Tandem mini circuit breaker, QO, 2 x 1 pole at 20A, 120/240VAC, 10kA, plug in mount





Main Product Miniature circuit-breaker Range QO Current Rating 20 A Voltage Rating 120/240 V AC Mounting Type Plug-in Number of Poles 1P Circuit Breaker Type Tandem

HACR rated

Pressure plate

\sim									
	\sim r	n	n	\sim	m	Δ	าช	. ~	r\/
	UJI		U)	•		C1	-11	$\boldsymbol{\alpha}$	rv
_	•		т.	_		•			

Li Di'	40 1 4 400/040 1/4 0 50/00 1/	
Interrupt Rating	10 kA 120/240 V AC 50/60 Hz	
Number of Panel Spaces	1	
Wire Size	AWG 14AWG 8 copper	
	AWG 12AWG 8 aluminium	
Tightening Torque	44.25 lbf.in (5 N.m) 0.020.04 in² (1025 mm²) (AWG 8AWG 2)	
Height	3.23 in (82 mm)	
Width	0.75 in (19 mm)	_
Depth	2.91 in (74 mm)	
Net Weight	0.35 lb(US) (0.159 kg)	

Ratings

Electrical Connection

Environment

Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

Ordering and shipping details

Category	00004-QO,QOT 10-30A 1P;10-60A 2P	
Discount Schedule	DE2A	
GTIN	785901418085	
Returnability	Yes	
Country of origin	MX	

Packing Units

r doming office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.30 in (8.382 cm)	
Package 1 Width	0.70 in (1.778 cm)	
Package 1 Length	3.40 in (8.636 cm)	
Package 1 Weight	5.61 oz (159.0 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	3.80 in (9.652 cm)	
Package 2 Width	0.70 in (1.778 cm)	

Package 2 Length	7.60 in (19.304 cm)
Package 2 Weight	3.36 lb(US) (1.524 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	8.20 in (20.828 cm)
Package 3 Width	8.30 in (21.082 cm)
Package 3 Length	19.80 in (50.292 cm)
Package 3 Weight	34.95 lb(US) (15.853 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty	18 months
----------	-----------