



Main

Product	Surge protection device
Range	Surge Breaker QO

Complementary

Surge Current	22.5 kA
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
MCOV	150 V 300 V
SCCR	22 kA
Local Signalling	1 LED green normal operation
Product destination	Load center QO
Height	3.7 in (93.98 mm)
Width	1.5 in (38.10 mm)
Depth	2.6 in (66.04 mm)

Environment

Enclosure Rating	NEMA 2
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08461-SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	785901210894
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.70 in (4.318 cm)
Package 1 Width	3.00 in (7.62 cm)
Package 1 Length	5.50 in (13.97 cm)
Package 1 Weight	10.40 oz (294.835 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20

Package 2 Height	6.10 in (15.494 cm)
Package 2 Width	6.60 in (16.764 cm)
Package 2 Length	16.70 in (42.418 cm)
Package 2 Weight	13.07 lb(US) (5.928 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------