

ILUKON PRO LED MR16 DIM

PARA USO GENERAL



CRI

IRC

80

VIDA Hrs

LIFE Hrs

25.000

ANGULO

ANGLE

40°

EFICACIA

EFFICACY

71lm/w

F. POTENCIA

POWER FACTOR

≥0,70

VOLTAJE

VOLTAGE

120V

DIM

BASE

BASE

GU10



ILUKON
PROFESSIONAL LIGHTING



Especificaciones Fotométricas / Photometric Specifications

Código/ Code	Watts/ Watts	Flujo Luminoso LED/ Luminous Flux LED	Temp. Color / CCT	Voltaje entrada/ Input Voltage	Factor de Potencia/ Power Factor	Vida útil hrs/ Lifetime hrs	Eficiencia/ Efficacy
95007300F	7W	500 Lm	3000 K	120V	0.70	25.000	71 LPW
95007500F	7W	500 Lm	5000 K	120V	0.70	25.000	71 LPW

NOTA: GLS se reserva el derecho de modificar o revisar las especificaciones técnicas sin previo aviso.

NOTE: GLS reserves the right to modify or revise technical specifications without prior notice.

Contacto: www.gls-ca.com / mail: contact@gls/ca.com / tel: (506) 2434-1212 y (506) 2228-2222.

GLS
GLOBAL LIGHTING
SOLUTIONS S.A.
Master Distributor