

ILUKON PRO LED A19 DIM

PARA USO GENERAL



CRI
IRC

80

VIDA Hrs
LIFE Hrs

15.000

ANGULO
ANGLE

220°

EFICACIA
EFFICACY

87lm/w

F. POTENCIA
POWER FACTOR

≥0,70

VOLTAJE
VOLTAGE

120V

DIM



ILUKON
PROFESSIONAL LIGHTING



Especificaciones Fotométricas / Photometric Specifications

Código/ Code	Watts/ Watts	Flujo Luminoso LED/ Luminous Flux LED	Temp. Color / CCT	Voltaje entrada/ Input Voltage	Factor de Potencia/ Power Factor	Vida útil hrs/ Lifetime hrs	Eficiencia/ Efficacy
95019098F	9W	800 Lm	3000 K	120V	0.70	15.000	88 LPW
95019097F	9W	800 Lm	6000 K	120V	0.70	15.000	88 LPW
95019153F	12W	1050 Lm	3000 K	120V	0.70	15.000	87 LPW
95019157F	12W	1050 Lm	6000 K	120V	0.70	15.000	87 LPW

NOTA: GLS se reserva el derecho de modificar o revisar las especificaciones técnicas sin previo aviso.

NOTE: GLS reserves the right to modify or revise technical specifications without prior notice.

Contacto: www.gls-ca.com / mail: contact@gls/ca.com / tel: (506) 2434-1212 y (506) 2228-2222.

GLS
GLOBAL LIGHTING
SOLUTIONS S.A.
Master Distributor