

# TUBO LED T8 96" 36W UL

PARA USO GENERAL



CRI IRC	VIDA Hrs LIFE Hrs	ANGULO ANGLE
83	40.000	240°
EFICACIA EFFICACY	F. POTENCIA POWER FACTOR	VOLTAJE VOLTAGE
125lm/w	≥0,90	120-277V



**ILUKON**  
PROFESSIONAL LIGHTING

## Descripción

Tubo LED de 96" para 36W de consumo, con apertura de 240 grados, carcasa de vidrio recubierto de PET.

## Description

LED tube 96", 36W consumption, beam angle 240 degrees, PET coated-glass housing

## Dimensiones/ Dimensions

Watts/ Watts	Código/ Code	Largo/ Length	Unidades por caja/ Units per box
36W	23203608A	240 cm	16

## Especificaciones Fotométricas / Photometric Specifications

Watts/ Watts	Código/ Code	Flujo Luminoso LED/ Luminous Flux LED	Temp. Color/ CCT	Voltaje Entrada/ Input Voltage	Factor de Potencia/ Power Factor	Vida útil Hrs/ Lifetime Hrs	Eficiencia/ Efficacy
36W	23203608A	4500Lm	6500K	120-277V	0.90	40.000	125 LPW

NOTA: GLS se reserva el derecho de modificar o revisar las especificaciones técnicas sin previo aviso.  
NOTE: GLS reserves the right to modify or revise technical specifications without prior notice.

Contacto: [www.gls-ca.com](http://www.gls-ca.com) / mail: [contact@glsc.ca.com](mailto:contact@glsc.ca.com) / tel: (506) 2434-1212 y (506) 2228-2222.

**GLS**  
GLOBAL LIGHTING  
SOLUTIONS S.A.